

NCR SelfServ Coin Dispense Sidecar

Looking to a solution to automate rolled coin dispense in your branches?

Scalable and secure coin dispense

The coin dispense sidecar attaches to your NCR SelfServ™ 80 Series ATM, removing the inconvenience of dealing with rolled coin dispense transactions at your branch counters. Your business and personal banking customer can receive change orders, note for coin exchanges, or rolled coins with speed, accuracy and confidence with speed, accuracy and confidence.

Greater configurability

Configurable to single or multi-currency, the sidecar offers all your customers a new range of secure and convenient transactions. Smaller footprint module which minimizes wasted space for rarely used coin denominations. Maximize uptime and availability by reducing the need for replenishments.

With more smaller coin magazines, this means greater configurability – maximizing the most optimal coin denominations. By adding coin dispense to your self-service channel, you can migrate time-consuming transactions away from the teller line, leaving your staff to focus on other high value activities.

Flexible and modular

The coin dispense sidecar has flexible placement options, giving you the freedom to locate it where it makes the most sense.

The modular nature means that if the initial placement option doesn't meet your business case, the slimline sidecar can be easily relocated to a more optimal location where there is a SelfServ ATM. Options also exist for future capabilities to be added to the self-service channel.



Why rolled coin dispense?

- On average up to 15% of all global teller transactions still involve processing bulk coin
- The average teller handles around 480 coin transactions each month
- Processing coin transactions can take x2 the time at the teller vs. other transactions

Key features

- Placement: Lobby or TTW
- Capability: Rolled Dispense + ATM
- Capacity Range: Minimum 495 rolls. Maximum Up to 726 rolls
- Denominations: 33 Maximum, Up to 15 rolls per dispense cycle
- Operating Mode: Online
- Software: Windows 7/10, XFS Release Package
- Display: 15" or 19" with multi-touch
- Safe: 3mm Steel Enclosure, UL347 Lock

Key functionality

- 3 x 11 magazine layout
- Freely configurable magazines
- Adjustable denomination capacity - tailored to specific locations (with minimal hardware and software impact)
- Online withdrawal
- Lower weight magazines
- "Note for coin" capability (using ATM)
- "Money change" functionality
- Change order automation USB Connection, Authenticate via ATM
- Greater uptime
- Patented technology
- User guidance MEIs

Technical specifications

Product dimensions

• HEIGHT*	38.1"	(1,020mm)
• WIDTH	21.2"	(530mm)
• DEPTH	35.1"	(863mm)
• WEIGHT		
Empty		(156kg)
When full Max Weight		(311kg)
15 rolls/rack, 0,312 kg/roll, 33 racks (reference: 0,50 € = 155 kg)		

Currency accepted

- Handles all major global currencies

Capacity

- Maximum Capacity – Up to 726 Rolls
- 11 layers, 3 slots
- 33 Max coin rolls per Top Roll
- 15 maximum coin rolls per dispense cycle / 5 rack per column (depends on denomination)

Servicing

- Rear access only
- Fill level indicators (green, orange, red) to easily locate empty magazines and module "state of health"
- CIT friendly due to automatic inventory management, reducing refilling time
- No manual entry required for refill of partial rolls

Security

- 3mm steel enclose safe with UL347 lock

Power requirements

- Voltage 24V DC
- Power consumption: Standby 6 Watt. Transaction 70 Watt

Temperature Range

- In operation: 0c to +55c
- Storage and transport: -40c to +55c
- Relative humidity: 20% - 80%, non-condensing

Additional Features

- USB connector for communication between sidecar and parent ATM
- XFS online support
- Windows 10 - Depending on parent ATM
- Freely configurable magazines
- Multi-denomination capability
- Online withdrawal
- Note for coin capability
- Automated the ordering of rolled coin for change orders

**Please note - For any coin sidecars alongside a through-the-wall (TTW) SelfServ ATM (such as SelfServ 84), such deployments must be inside of a branch lobby or vestibule location and not an exterior environment.*

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

All brand and product names appearing in this document are trademarks, registered trademarks or service marks of their respective holders.

© 2020 NCR Corporation Patents Pending

081820_PM-FIN_0820 ncr.com

